

THIS BOX CONTAINS:

- 80 CU. FT. ARGON/CO2 MIX CYLINDER (EMPTY)
- AMERICAN MADE HEAVY-DUTY WELDING CART

FIREPOWER MIG WELDING SYSTEM

- MIG WELDING GLOVES
- MIG WELDING SLEEVES
- MIG PLIERS
- GASPONY WELDING HOOD
- W/ AUTO DARKENING VARIABLE SHADE LENS
- SPATTER BRUSH
- GASPONY DOO RAG
- (2) .023/8mm REPLACEMENT TIP
- (1) REPLACEMENT NOZZLE



1. Packaging separates into two parts.
2. Remove tape and slide top of package from the bottom tray.
3. Remove product from bottom tray.
4. Properly discard box and packaging material.
5. Read all enclosed product literature and follow all safety precautions.

UNPACKING
INSTRUCTIONS

PLEASE READ REVERSE AND
ALL ENCLOSED PRODUCT
LITERATURE PRIOR TO USE

NOTICE:

CALL or visit us **ONLINE** to find a **Welding Gas To Go!** purchase and exchange location near you and for information on our other welding products



877-GAS-PONY gaspony.com

AMERICA'S LARGEST PACKAGED GAS PURCHASE AND EXCHANGE PROGRAM

With normal care and storage, the MIGPONY Welding System will provide years of quality service. Always maintain cylinder in the recommended upright position. Replace cylinder cap when cylinder is not in service and when transporting. The following safety overview should be read in addition to the supplied manufacturer **Operating Instructions** for the Firepower MIG Welding System before use of this product and should be kept for reference use.

American Made Heavy-Duty Welding Cart

Use caution when using the cart, for transporting and storing the cylinder. Follow all safety procedures regarding the safe use of this cart. Specs: 24" height x 16" width x 43" depth. 53 lbs

#3 Argon/CO2 Mix Cylinder (empty)

80 cu.ft Capacity

Before using this cylinder you should familiarize yourself with the MSDS for Argon and CO2. The MSDS is available under "safety" at www.gaspony.com. Use caution when using, transporting and storing this cylinder. Follow all safety procedures regarding the safe use of this gas.

Safety Overview: Argon/CO2 Mix gas is stored in your cylinder at high pressure (2000 PSI). Argon/CO2 Mix is a non-flammable gas that rapidly supports combustion of any type. If high levels of Argon/CO2 Mix gas are present, any combustible material will catch on fire much more rapidly and burn vigorously as long as Argon/CO2 Mix is present. Caution should be used within this cylinder because the gas is stored at high pressure. Care must be used when opening and closing the cylinder valve. Please refer to the manufacturer's safety procedures included with your Firepower MIG Welding System when connecting a regulator to the cylinder valve. Always keep valve protection caps in place whenever cylinders are moved or stored (full or empty).



Firepower MIG Welding System

Safety Overview: Be sure to read all inclosed safety and instructional material supplied with the Firepower MIG Welding System.

Warning: DO NOT USE OIL, OIL BASED PRODUCTS OR GREASE ON VALVE OR GAS CONNECTIONS.

CAUTION Cylinders when full are highly pressurized. Always handle with care. Never allow cylinders to be dropped, knocked over or subjected to excessive heat. When moving cylinders, always be certain that valve protection caps are secured in place. Place valve protection caps where they are easily found. Replace cap when cylinders are empty.

CAUTION
Read enclosed operating instructions thoroughly and carefully before operating this equipment.

WARNING
This product, when used for welding or cutting, produces flames or gases which contain chemicals known to the State of California to cause birth defects and, in some cases, cancer.

(California Health & Safety Code §25249.5 et seq.)



THOROUGHbred
INDUSTRIAL CYLINDER EXCHANGE®