

# 物质安全技术说明书

## MATERIAL SAFETY DATA SHEET

中文名称: 免维护铅酸蓄电池 FM12200(12V20Ah/20hr)

英文名称: Lead-acid Battery FM12200(12V20Ah/20hr)

宁波海湖蓄电池有限公司



**NINGBO SEALAKE STORAGE BATTERY CO.,LTD.**

**MATERIAL SAFETY DATA SHEET**

**LEAD-ACID BATTERY FM12200(12V20Ah/20hr)**

**SECTION1 PRODUCT AND COMPANY IDENTIFICATION**

**Product name:** Lead-acid Battery FM12200(12V20Ah/20hr)  
**Company :** Ningbo Sealake Storage Battery Co. , Ltd .  
**Address :** Linshan Town , Yuyao City , Zhejiang Province,315461,P.R . China  
**E-mail :** kerwin@sealake.com  
**Fax:** 86-571-88994566  
**Emergency Phone:** 86-571-88999299

**SECTION2 INFORMATION ON INGREDIENTS**

**Product name:** Lead-acid battery FM12200(12V20Ah/20hr)

<b>Ingredient</b>	<b>Concentration</b>	<b>CAS No.</b>	<b>EC No</b>	<b>Hazardous label</b>
Pb	/	7439-92-1	231-100-4	T
PbO2	/	1309-60-0	215-174-5	O,T,N
Plastic	/	/	/	/
H <sub>2</sub> SO <sub>4</sub>	/	7664-3-9	231-639-5	C

**SECTION 3 HAZARDS IDENTIFICATION**

**Hazards Identification:** The battery has passed the vibration test, pressure differential test and leakage test at 55°C according to Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations (15<sup>th</sup>)SPECIAL PROVISION 238. It is not restricted to IATA DGR according to special provision A67 and is not restricted to IMDG CODE according to special provision 238 .

**Emergency Overview:** The internal battery materials may cause severe irritation to eyes and skin. Causes burns.

#### SECTION4 FIRST - AID MEASURES

**Skin Exposure:** If the internal battery materials of an opened battery cell come into contact with the skin, immediately flush with plenty of water for at least 15 minutes. Seek immediate medical attention.

**Eye Exposure:** In case of contact the electrolyte contained inside the battery with eyes, flush with copious amounts of water for at least 15 minutes . Assure adequate flushing by separating the eyelids with fingers. Seek immediate medical attention.

**Inhalation Exposure:** If potential for exposure to mist or dusts occurs, remove immediately to fresh air and seek medical attention.

**Oral Exposure:** If swallowed, do not induce vomiting . Seek immediate medical attention ,

#### SECTION5 FIRE FIGHTING MEASURES

**Extinguishing Media :**

Suitable: water spray, Dry chemical, Sandy soil , Carbon dioxide or appropriate foam .

**Firefighting:**

protective Equipment wear self contained breathing apparatus and protective clothing to prevent contact with skin and eyes .

Specific hazards: Emit toxic fumes under fire conditions .

#### SECTION6 ACCIDENTAL RELEASE MEASUREES

If batteries show signs of leaking, avoid skin or eyes contact with the material leaking from the battery . Use chemical resistant rubber gloves and non-flammable absorbent materials, for clean up. Mix with inert material (e.g. dry sand, vermiculite) and transfer to sealed container for disposal.

#### SECTION7 HANDLING AND STORAGE

**Handling**

Keep away from ignition sources, heat and flame. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Avoid mechanical or electrical abuse and overcharge. More than a momentary short circuit will generally reduce the battery service life. Avoid reversing battery polarity within the battery assembly. In case of a battery unintentionally be crushed, acid resistant gloves must be used to handle all battery components. Avoid contact with eyes, skin. Avoid inhalation. No smoking at working site. Materials to Avoid: Strong oxidant, Corrosives, Storage:

Store in a cool, well-ventilated area. Keep away from ignition sources, heat and flame. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Materials to Avoid: Strong oxidant, Corrosives.

### SECTIONS 8 EXPOSURE CONTROL/PPE

**Engineering Controls:** Use ventilation equipment if available. Safety showers and eye bath.

**Personal Protective Equipment:**

**Respiratory:** Wear government approved respirator.

**Eye:** Chemical safety glasses.

**Clothing:** Wear appropriate protective clothing.

**Hand:** Wear acids resistant gloves.

**Other Protect:** No smoking, drinking and eating at working site, Wash thoroughly after handling.

### SECTION 9 PHYSICAL/CHEMICAL PROPERTIES

**Appearance:** Black square plastic cement shell (containing electrolyte)

**Odor:** odorless

**MP/MP Range:** > 300 °C

**Solubility :** Partial soluble in water      pH: 1~2

### SECTION10 STABILITY AND REACTIVITY

**Stability:** Stable under normal temperatures and pressures.

**Materials to Avoid:** Strong oxidant, Corrosives.

**Conditions to Avoid:** Avoid exposure to heat and open flame. Avoid mechanical or electrical abuse and overcharge. Prevent short circuits. Prevent movement which could lead to short circuits.

**Hazardous Polymerization:** Will not occur.

**Hazardous Decomposition Products:** Sulfur oxides, Sulfuric acid mist , Metal oxides.

### SECTION11 TOXICOLOGICAL INFORMATION

**Toxicity Data:** Not available.

**Irritation Data:** The internal battery materials may cause severe irritation to eyes and skin. Causes burns.

**Carcinogenicity:** The International Agency On Cancer (LARC) has classified "strong inorganic and mists containing sulfuric acid " as a category 1 carcinogen (inhalation),a substance that is carcinogenic to humans. This classification does not apply to the sulfuric acid contained within the battery. Misuse of the product ,such as overcharging, may result in the generation of sulfuric acid mist at high levels.

### SECTION12 ECOLOGICAL INFORMATION

Lead and its compounds can result in a threat if released into the environment.

In most surface water and groundwater, lead forms compounds with anions such as hydroxides, carbonates, sulfates, and phosphates, and precipitates out of the water column. Lead may occur as sorbed ions or surface coatings on sediment mineral particles or may be carried in colloidal particles in surface water. Most lead is strongly retained in soil, resulting in little mobility. Lead may be immobilized by ion exchange with hydrous oxides or clays or by chelation with humic or fulvic acids in the soil. Lead (dissolved phase) is bioaccumulated by plants and animals, both aquatic and terrestrial.

### SECTION13 DISPOSAL CONSIDERATIONS

#### Appropriate Method of Disposal of substance:

Lead-acid batteries are completely recyclable. Return whole scrap batteries to distributor, manufacture or lead smelter for recycling. For neutralized spills, place residue in acid-resistant containers with sorbent material, sand or earth and dispose of in accordance with local, state and federal regulations for acid and lead compounds. Contact local and/or state environmental officials regarding disposal information.

### SECTION14 TRANSPORT INFORMATION

The battery has passed the vibration test, pressure differential test and leakage test at 55 °C according to Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations (15<sup>th</sup>), SPECIAL PROVISION 238.

#### LATA

Proper Shipping Name: /

UN Number: /

Hazard Class: /

Packing Group: /

#### IMO

Proper Shipping Name: /

UN Number: /

Hazard Class: /

Packing Group: /

### SECTION15 REGULATORY INFORMATION

#### EU Additional Classification:

S36/37

Safety Statements: Wear suitable protective clothing and gloves.

